

Par-Kut International CENTRY

Partial Listing of Available Options

CANOPY: Overhangs can range from None to 36". Fascia can range from minimum required for devices, up to 25". The 25" fascia is a split fascia used to conceal view of optional roof mounted air conditioner.

CASHIER CONVENIENCES: Slide-up, side sliding full height, or energy saving style cashier windows. Transaction drawers, deal trays, intercoms and ticket windows.

CASH MANAGEMENT: Locking cash drawers and drop safes.

CLEARANCE ISSUES: Removable lifting rings and custom heights for low clearance applications.

CLIMATE CONTROL: Through wall cool only or combination heat/cool type or roof mounted air conditioner units. Additional or higher watt output heaters. Package HVAC units.

CORROSION BARRIERS: Stainless steel base.

CUSTOM EXTERIORS: Two-color paint, EIFS (Exterior insulation and finish system), logos and vinyl signage.

DOORS: Steel hinged door, with three ball bearing full mortise hinges with non-removable pins. Hinged door(s) shall include appropriately sized hydraulic closer (unless owner or code circumstances over-rule). Cylindrical type entrance lockset is standard.

ELECTRICAL: Load centers with higher amperage main disconnects and additional circuit breaker spaces. 3-Phase load centers, mini power-zones or transformers. Factory installed junction boxes and raceways for future field installed fire, security or communications equipment.

FLOORING: Vinyl composite floor tile, sheet vinyl or carpet mounted on 3/4" exterior grade plywood sub floor; Lay in anti-fatigue mat (for buildings 4' or 5' wide only).

GLAZING: Tinted or Low-e or reflective or insulated safety glass or break resistant acrylic sheet or unbreakable polycarbonate.

INSULATION: Additional insulation in ceiling, floors and walls for severe weather areas.

LIGHTING: Recessed interior fluorescent lights, dimming incandescent down lights, fluorescent lighting under canopy overhang, single or duplex lamp exterior floodlights and traffic signal lights.

NOISE MANAGEMENT: Acoustical tile ceiling, sound deadening walls, laminated glass.

RECEPTACLES: Additional electrical outlets, isolated ground, surge suppression and ground fault interrupt receptacles.

VENTILATION: Exhaust fans (specify CFM) and louvers, ventilation windows with insect screen located per drawing.

WINDOWS: Radius corner window openings.

WORK COUNTER: Plastic laminate or stainless steel upgrade or additional work counter.