



- COUNTER- OPTIONAL 24' DEEP, PAINTED GALVANIZED STEEL, OPTIONAL 38' ABOVE FLOOR, WITH STORAGE DRAWER BENEATH.
- DOOR- OPTIONAL 36' WIDE, SWINGING STEEL WITH SAFETY GLAZING, WEATHER-STRIPPING, BALL BEARING BUTTS, HYDRAULIC CLOSER, LOCK, HARDWARE & OPTIONAL 24" X 12" OPTIONAL VENT 2-REQ'D.
- DUPLEX DUTLET 1-REQ'D, ADDITIONAL OPTIONAL.
- OPTIONAL SINGLE RECEPTACLE FOR OPTIONAL AIR CONDITIONER.
- SWITCH FOR LIGHT AND OPTIONAL EXHAUST FAN IN 8' X 8' ROOM.
- SWITCH FOR LIGHT AND OPTIONAL EXHAUST FAN IN 4' X 8' ROOM.
- 7. LIGHT- FLUORESCENT LIGHT FIXTURE, 2-REQ'D.
- OPTIONAL EXHAUST FAN- MOUNTED THROUGH WALL, 170CFM 2-REQ'D.
- OPTIONAL COMBINATION HEAT/COOL UNIT- GE ELECTRIC MODEL# AJJ11D 230V./11,000BTU WITH INTEGRAL THERMOSTAT CONTROL.
- OPTIONAL 3/4" NIPPLE- THRU WALL TO C.B. PANEL FOR ELECTRICAL SERVICE ENTRANCE. CIRCUIT BREAKER PANEL- 120/240V. WITH GROUND BAR AND 100AMP MAIN BREAKER.
- ANCHOR CLIPS- 2" X 2" WELDED TO BASE AT GRADE, WITH 3/4" ANCHOR BOLT HOLE, 4-REQ'D. DNE EACH CORNER ANCHOR BOOTH AFTER FINAL LOCATION, ANCHOR BOLTS NOT INCLUDED.

NOTE: PAR-KUT BOOTHS ARE OF SINGLE UNIT WELDED GALVANIZED STEEL CONSTRUCTION, FACTORY ASSEMBLED AND DELIVERED SET UP. FAILURE TO SECURELY ANCHOR BOOTH MAY RESULT IN OVERTURNING OF UNIT AND SERIOUS INJURY TO OCCUPANT.

- GLAZING TO BE OPTIONAL 1" CLEAR TEMPERED INSULATED SAFETY GLASS SET IN CLEAR ANODIZED ALUMINUM WINDOW FRAMES. MAKE-UP TO BE TWO PIECES OF 1/4" CLEAR TEMPERED GLASS WITH 1/2" AIRSPACE.
- PAINT- RUST INHIBITIVE PRIMER WITH AN INDUSTRIAL FINISH.
- ELECTRICAL- ALL WIRING BY PAR-KUT TO BE #12(MIN) STRANDED COPPER, THHN ENCLOSED IN 1/2"(MIN) E.M.T. PER NATIONAL ELECTRIC CODE. FITTINGS, FIXTURES AND DEVICES ARE U.L. LISTED. ALL WIRING TO TERMINATE AT C.B. PANEL. ALL CIRCUITS HAVE GREEN GROUND WIRE.
- LIFTING RING(S) PROVIDED IN ROOF.
- E. NO ON SITE WORK BY PAR-KUT.

